AMENDMENTS TO THE CLAIMS

In the claims, please make the following amendments:

- 1-2. (Canceled)
- 3. (Currently Amended) The A male urinary system of claim 1 further comprising:
 - a penis/urinary collection interface unit, said penis/urinary collection interface unit comprising a primary receiver unit for accommodating a male penis during urination, configured for juxtaposition to and temporary seating against the adjacent pubic area and comprised of substantially rigid material, and a secondary containment unit wherein said primary receiver unit is at least partially nested with proximal margins of said secondary containment unit and said primary receiver unit being fused to said secondary containment unit to prevent fluid ingress or egress past a line of fusion between said primary receiver unit and said secondary containment unit, said primary receiver unit being position relative to said secondary containment unit whereby a gap is formed between the outer surface of said primary receiver unit and the inner surface of said secondary containment unit, said gap extending at least from the distal end of said primary receiver unit and said line of fusion between said secondary containment unit and said primary receiver unit, said primary receiver unit opening at its distal end into said secondary containment unit near the distal end of said secondary containment unit;
 - a conduit means attached to said distal end of said secondary containment unit for collecting urine flowing from said distal end of said primary receiving unit;

2

- a urine receptacle means for receiving urine which flows through and from said conduit;

 and
- a secondary spill proof mechanism where a proximate end of said primary receiver unit receiving the penis has an elevated edge at the juxtaposition with said pubic area rising from said line of fusion, said elevated edge being configured to facilitate prevention of even minor backflow.
- 4. (Currently Amended) The male urinary system of elaim 2 claim 3 further comprising a snap

 fit lid in combination with said primary receiver unit which closes and substantially seals

 the penis/urinary collection between uses. a secondary spill-proof mechanism where a

 proximate end of said primary receiver unit receiving the penis has an elevated edge at

 the juxtaposition with said pubic area rising from said line of fusion, said elevated edge

 being configured to facilitate prevention of even minor backflow.